

Filter Cartridge with 3 Lugs Cap



Media Types:

- 100% cellulose, blend media
- Spun bond polyester

Features:

- Aluminium top with 3 lugs for secure filters
- Greatest filter area
- Highest filtration efficiencies
- Best pulse clean effects on cartridges

Construction:

- Top/Bottom caps: Aluminum top with 3 lugs
- Filter surface: various available
- Inner core: galvanized mesh
- Outer core: galvanized mesh / strip bands
- Gasket: urethane gasket to ensure airtight sealing

Compressed Air Requirements

- 70-100 psi (5-7 bar)

Application:

- Metal working, Fume, Powder coating
- Shot Blasting, Mixing, Grinding
- Mining industry, Chemical

Standard Dimensions:

Model	Al Lug Center	End Cap	Length (mm)	Filter Area (Cellulose Media)	Filter Area (Polyester Media)
HS/AL3266	390mm	324mm	660mm	21.00m ²	9.40m ²
HS/AL3275	390mm	324mm	750mm	26.00m ²	10.70m ²
HS/AL3288	390mm	324mm	880mm	27.00m ²	12.50m ²
HS/AL3290	390mm	324mm	915mm	28.00m ²	13.00m ²
HS/AL32130	390mm	324mm	1300 mm	41.00 m ²	18.50 m ²

Both the size of the cartridge and the shape of the caps are available to meet the optimum performance of your applications.

Add: 1 GuoTai Road, Zhangjiagang, Jiangsu Province, China P.C.: 215600

Tel: +86-512-5868 5979 Fax: +86-512-5898 6893

www.industrialcleanair.com

Email: airmaxfilter@yahoo.com.cn MSN: fullcart@hotmail.com