

Filter Cartridge with Square Cap



Top & Bottom
installation

Media Types:

- 100% cellulose, blend media
- Spun bond polyester

Features:

- Square flange top for secure filters
- Highest filtration efficiencies to 99.98%
- Best pulse clean effects on cartridges

Construction:

- Top/Bottom caps: electro galvanized plates
- Filter surface: various available
- Inner core: galvanized mesh
- Outer core: galvanized mesh / strip bands
- Gasket: urethane gasket to ensure airtight sealing

Compressed Air Requirements

- 70-100 psi (5-7 bar)

Application:

- Metal working, Fume, Powder coating
- Shot Blasting, Mixing, Grinding, Mining industry, Chemical
- Replacement Filter for Farr Gold Series® dust collectors!

Dimensions available:

Model	Top Cap	End Cap	Length (mm)	Filter Area (Cellulose Media)	Filter Area (Polyester Media)
HS/S3266	363X406 mm	324mm	660mm	21.00m ²	9.40m ²
HS/S3275	363X406 mm	324mm	750mm	26.00m ²	10.70m ²
HS/S3288	363X406mm	324mm	880mm	27.00m ²	12.50m ²
HS/S3290	363X406mm	324mm	915mm	28.00m ²	13.00m ²

Both the size of the cartridge and the shape of the caps are available to meet the optimum performance of your applications.

Add: 1 GuoTai Road, Zhangjiagang, Jiangsu Province, China P.C.: 215600

Tel: +86-512-5868 5979 Fax: +86-512-5898 6893

www.industrialcleanair.com

Email: airmaxfilter@yahoo.com.cn MSN: fullcart@hotmail.com