

### Pleated Bag Filter



#### Features:

- 100% Spun Bond Polyester
- Up to 100-200% more filtration area than traditional filter bags.
- Excellent withstanding performance to pulse jet
- Fits most existing tube sheet designs, simple and easy installation and maintenance

#### Construction:

- Top cap: roll flange steel / aluminum / PU
- End cap: steel / aluminum / PU
- Filter surface: various available
- Inner core: perforated steel
- Outer strip band as reinforcement
- Maximum length: 2000mm

#### Chemical Resistance:

- Oil and water resistance: Good
- Hydrolysis resistance: Fair
- Acid resistance: Good
- Alkaline Resistance: Fair

#### Dust Release:

- Excellent

#### Applicable Temperature:

- Moisture 90°C, Dry 120°C



#### Standard Dimensions:

Model	O.D. (mm)	Length (mm)	Filter Area (m2)
HS/L1210	124	1000	1.80
HS/L1510	153	1000	2.30
HS/L1520	153	2000	4.60
HS/L1410	146	1000	2.30
HS/L1420	146	2000	4.60

#### Application:

- For the rebuilding of conventional bag house
- Matching new style pulse jet bag dust collectors.

Add: 1 GuoTai Road, Zhangjiagang, Jiangsu Province, China P.C.: 215600

Tel: +86-512-5868 5979 Fax: +86-512-5898 6893

[www.industrialcleanair.com](http://www.industrialcleanair.com)

Email: [airmaxfilter@yahoo.com.cn](mailto:airmaxfilter@yahoo.com.cn) MSN: [fullcart@hotmail.com](mailto:fullcart@hotmail.com)