

Antistatic Filter Cartridges



Application:

- Metal, Wood, Chemical,
- Cement, Food Paper, Plastic
- Shot Blasting
- Foundry Dust
- Powder, Mineral Processing

Features:

- Filter media: Antistatic Polyester
- Source of media: Germany, Japan or China local suppliers
- Excellent resistance against electric conductance

Construction:

- Top cap: open steel plate, no rust
- End cap: open or closed steel plate, no rust
- Filter surface: various available
- Inner core: galvanized mesh
- Outer strip band: one piece as reinforcement
- Gasket: specialty rubber to ensure airtight sealing

Chemical Resistance:

- Oil and water resistance: good
- Hydrolysis resistance: Good
- Acid resistance: Good
- Alkaline Resistance: Good

Dust Release:

- Excellent

Applicable Temperature:

- Moisture 90°C, Dry 120°C

Dimensions:

Model	O.D. (mm)	I.D. (mm)	Length (mm)	Filtration surface (m ²)
HS/A3266	324	213	660	9.40
HS/A3566	352	241	660	9.40
HS/A3275	324	213	750	10.70
HS/A3288	324	213	880	12.50
HS/A3290	324	213	915	13.00

Both the size of the cartridge and the shape of the caps are available in various specifications. All configurations are changeable to meet the optimum performance of your applications. Please contact us directly for more technical information.

Add: 1 GuoTai Road, Zhangjiagang, Jiangsu Province, China P.C.: 215600

Tel: +86-512-5868 5979 Fax: +86-512-5898 6893

www.industrialcleanair.com

Email: airmaxfilter@yahoo.com.cn MSN: fullcart@hotmail.com