

Farr Replacement Filter Cartridges



**Top & Bottom
installation**

Application:

- For Farr Gold Series® dust collectors!

Media types:

- 100% cellulose, blend media
- Spun bond polyester

Features:

- High efficiency air filter media for Farr dust collectors
- Top and bottom installation available
- Easy installation of filters
- Customized specifications available.

Construction:

- Top cap size: 362X402 / 380X364
- Top & End cap material: closed electro galv. steel plate, no rust
- Filter surface: various available
- Inner core: galvanized mesh
- Outer core: galvanized mesh or strip bands
- Gasket: specialty rubber to ensure airtight sealing

Compressed Air Requirements

- 70-100 psi (5-7 bar)

Dimensions available:

Model	Top Caps	O.D./I.D. (mm)	Length (mm)	Filtration surface(m ²)
HS/Fa3266	362X402 / 380X364	324/213	660	21.00*
HS/Fa3275	362X402 / 380X364	324/213	750	26.00*
HS/Fa3288	362X402 / 380X364	324/213	880	27.00*
HS/Fa3290	362X402 / 380X364	324/213	915	28.00*

Both the size of the cartridge and the shape of the caps are available to meet the optimum performance of your applications. Please contact us directly for more technical information.

*: For cellulose filter media only!

Add: 1 GuoTai Road, Zhangjiagang, Jiangsu Province, China P.C.: 215600

Tel: +86-512-5868 5979 Fax: +86-512-5898 6893

www.industrialcleanair.com

Email: airmaxfilter@yahoo.com.cn MSN: fullcart@hotmail.com