

Pulse Pleat Filter Bags



Application:

- For the rebuilding of conventional bag house and matching new style pulse jet filters.

Features:

- 100% Spun Bond Polyester, white or black color
- Up to 100-200% more filtration area than traditional filter bags.
- Excellent withstanding performance to pulse jet
- Fits most existing tube-sheet designs, simple and easy installation and maintenance

Construction:

- Top cap: roll flange steel / aluminum with 3 lugs or holes
- End cap: closed electro galvanized steel plate, no rust
- Filter surface: various available
- Inner core: perforated steel
- Outer strip band: 1, 2 or 3 pieces as reinforcement
- Maximum length: 2000mm

Chemical Resistance:

- Oil and water resistance: Good
- Hydrolysis resistance: Fair
- Acid resistance: Good
- Alkaline Resistance: Fair

Dust Release:

- Excellent

Applicable Temperature:

- Moisture 90°C, Dry 120°C

Dimensions available:

Model	O.D. (mm)	Length (mm)	Filtration surface (m ²)
HS/L1210	124	1000	1.80
HS/L1510	153	1000	2.30
HS/L1520	153	2000	4.60
HS/L1410	146	1000	2.30
HS/L1420	146	2000	4.60

Standard top load and bottom load are available. The caps have various constructions such as: 3 lugs/holes aluminum, roll flange steel and 3 holes polyamide. Custom construction designs are available. All configurations are changeable to meet the optimum performance of your applications. Please contact us directly for more technical information.

Add: 1 GuoTai Road, Zhangjiagang, Jiangsu Province, China P.C.: 215600

Tel: +86-512-5868 5979 Fax: +86-512-5898 6893

www.industrialcleanair.com

Email: airmaxfilter@yahoo.com.cn MSN: fullcart@hotmail.com