

Spun Bond Polyester Filter Cartridges



Features:

- 100% Spun Bond Polyester, white or black color
- Best chemical resistance.
- Excellent moisture resistance and dust release
- Excellent withstanding performance to pulse jet
- Durable and rigid material, washable

Construction:

- Top cap: open electro galvanized steel plate, no rust
- End cap: open or closed galvanized steel plate, no rust
- Filter surface: various available
- Inner core: galvanized mesh for greatest airflow
- Outer strip band: two pieces as reinforcement
- Gasket: specialty rubber to ensure airtight sealing

Chemical Resistance:

- Oil and water resistance: Good
- Hydrolysis resistance: Fair
- Acid resistance: Good
- Alkaline Resistance: Fair

Dust Release:

- Excellent

Applicable Temperature:

- Moisture 90°C, Dry 120°C

Compressed Air Requirements

- 70-100 psi (5-7 bar)

Application:

- Metal, Wood, Chemical,
- Cement, Food, Paper,
- Pharmaceutical
- Welding Smoke
- Shot Blasting
- Foundry Dust
- Mineral Processing

Dimensions available:

Model	O.D.	I.D.	Length	Filter Area(m ²)
HS/P3266	324	213	660	9.40
HS/P3566	352	241	660	9.40
HS/P3275	324	213	750	10.70
HS/P3288	324	213	880	12.50
HS/P3290	324	213	915	13.00

Both the size of the cartridge and the shape of the caps are available in various specifications to meet the optimum performance of your applications. Please contact us directly for more technical information.



Add: 1 GuoTai Road, Zhangjiagang, Jiangsu Province, China P.C.: 215600

Tel: +86-512-5868 5979 Fax: +86-512-5898 6893

www.industrialcleanair.com

Email: airmaxfilter@yahoo.com.cn MSN: fullcart@hotmail.com