

Polyester + PTFE Filter Cartridges



Application:

- Filtration of very, very fine dust types in Chemical, Pigment, Al-pulver Welding Fume, Pharmaceutical and other sticky agglomerative dust collections.

Features:

- Filter media: Polyester + PTFE membrane
- Source of media: USA or China local suppliers
- Wide pleat spacing and smooth, hydrophobic PTFE provides excellent dust cake release
- Excellent resistance to chemical erosion

Construction:

- Top cap: open steel plate, no rust
- End cap: open or closed steel plate, no rust
- Filter surface: various available
- Inner core: galvanized mesh
- Outer strip band: two pieces as reinforcement
- Gasket: specialty rubber to ensure airtight sealing

Chemical Resistance:

- Oil and water resistance: Excellent
- Hydrolysis resistance: Very good
- Acid resistance: Good
- Alkaline Resistance: Good

Dust Release:

- Excellent

Applicable Temperature:

- Moisture 90°C, Dry 120°C

Dimensions available:

Model	O.D.	I.D.	Length	Filter Area(m ²)
HS/F3266	324	213	660	9.40
HS/F3566	352	241	660	9.40
HS/F3275	324	213	750	10.70
HS/F3288	324	213	880	12.50
HS/F3290	324	213	915	13.00

Both the size of the cartridge and the shape of the caps are available in various specifications to meet the optimum performance of your applications. Please contact us directly for more technical information.



Add: 1 GuoTai Road, Zhangjiagang, Jiangsu Province, China P.C.: 215600

Tel: +86-512-5868 5979 Fax: +86-512-5898 6893

www.industrialcleanair.com

Email: airmaxfilter@yahoo.com.cn MSN: fullcart@hotmail.com